



EASY INSTALLATION TIPS:

- MAY BE INSTALLED AT ANY TEMPERATURE
- MUST USE ¾ INCH -J- CHANNEL
- USE PREFERED ACCESSORIES
- ALWAYS USE RANDOM SIZE STARTER PIECES AT THE BEGINNING OF EACH COURSE
- ALWAYS BE SURE RANDOM STARTER PIECES ARE CUT LEAVING AT LEAST 1 INCH OF THE LOCK EXPOSED FOR THE FOLLOWING PANEL ENGAGEMENT
- ALWAYS BE SURE AT EVERY SEEM, THE PANELS ARE POSITIONED ON THE SMALL SCRIBED LINE PROVIDED AT THE COMPLETE RIGHT HAND SIDE OF THE NAIL HEM.
- INSTALL THE CENTER NAIL FIRST IN THE SMALL CIRCULAR HOLE LOCATED IN THE VERY CENTER OF THE PANEL, DO NOT NAIL TIGHT.
- INSTALL AT LEAST 7 NAILS PER FULL PANELS EVENLY SPACED THROUGHOUT, DO NOT NAIL TIGHT.
- BE SURE NAILS ARE LOCATED ON "CENTER" OF ALL OVAL SHAPED NAIL SLOTS.